



### Door & Jamb Reinforcement

The bolt buddy strengthens and protects the weakness of the door jamb, door, deadbolt and hinges. It prevents the burglar easy access by kicking and prying the door. The two steel bracket system is bolted from the inside to the outside of the door jamb. This system acts like a vise equalizing the stress of an attack over the entire door and door frame, helping to prevent the splitting of doors and door jambs.

Mfg#	Finish	EZ#
DWBOLT ANT	Antique Brass	039699
DWBOLT BRA	Brass	039700
DWBOLT BRO	Bronze	039701
DWBOLT CHR	Chrome	039702



### Hinge Removal Prevention Screws

The hinge screw is used to prevent closed doors from being removed from their hinges when the hinge pins are removed. A screw is removed from the door side of the hinge and the corresponding screw from the jamb side. The jamb side or door side (whichever is most convenient) then receives the Hinge screw. When the door is closed the protruding head of the screw enters the corresponding screw hole on the other hinge plate thus not allowing the hinges to pass one another when the hinge pins are removed. For use in steel or concrete frames use an appropriate sized expanding plug. The screw is adjustable to various penetrating depths into the jamb and the door to allow the maximum amount of the screw to engage the door and frame.

Mfg#	EZ#
DWHINGE SCR	039707



### 180 Degree Door Viewer

The door view is solid brass construction with an interior lens shutter. It has 180° glass optic lens to prevent fogging and allow more illumination for night viewing. The lens shutter prevents dust, etc. from collecting on the lens as well as restricting viewing from the exterior to the interior. Fits doors from 1 1/2" to 2 1/4" thick.

Mfg#	EZ#
DWVIEWER	039709